ASYMMETRIC PROPERTIES OF HEART RATE VARIABILITY TO ASSESS OPERATOR FATIGUE

Christian Heinze¹, Udo Trutschel², Dave Edwards³, Bill Sirois², & Martin Golz¹ ¹Faculty of Computer Science, University of Applied Sciences Schmalkalden, Germany ²Circadian Technologies, Inc., Stoneham, Massachusetts, USA ³Caterpillar, Inc., Peoria, Illinois, USA

Summary: The aim of this study is to evaluate the suitability of heart rate recordings for establishing a reliable connection to well-defined fatigue and performance measures in order to estimate fatigue in industrial and transportation applications. An overnight driving simulation scenario with partial sleep deprivation was utilized to induce strong fatigue. An experiment trial was divided into repeated sessions, each of which consisted of a driving performance and two vigilance tasks. Heart rate (HR) was recorded over the entire experiment; HRmeasures were derived and correlated against measures that were established from driving and vigilance task performance and that represent various aspects of operator fatigue. In a previous report (Hefner et al. 2009) we presented on the basis of the data of one volunteer that multiple fatigue measures correlate well with different expressions of heart rate variability (HRV), especially with longterm HRV derived from Poincaré plots. In this work, we intensify the Poincaré analysis by dividing the distribution of HR data in different accelerating and decelerating segments and by establishing properties of asymmetry between these segments. We also show that most of the properties of long-term HRV correlate well with specific fatigue measures for a group of 5 volunteers despite their large inter-individual differences in HR-to-fatigue correlations.

INTRODUCTION

Worker fatigue is a major concern for any operation that requires sustained employee alertness and performance, especially in industries where 24/7 shift work schedules are utilized, such as in mining, transportation and emergency services. During task performance, subjects have to expend physical and mental effort, which is usually reflected in increased heart rate (HR, number of heart beats in a certain time period) and decreased heart rate variability (HRV, phenomenon of varying time durations between heart beats, expression of balance between sympathetic and parasympathetic branch of autonomous nervous system) when compared to resting situations. In contrast to this, in a state of fatigue or relaxation HR will decrease and HRV will increase. Therefore, during periods where both workload and fatigue are high, HR measures can expose contradicting sensitivities. To add to this complexity, Coumel et al. (1995) pointed out that several HR measures show a strong circadian behavior under normal sleeping conditions. Therefore, a correlation to fatigue can be expected. As a consequence, the behavior of HR measures in general, and their ability to indicate fatigue in particular, can only be established under strict experimental conditions eliminating the influence of mental workload. In this experimental protocol of driving and testing (CTT and PVT), the mental workload and their influences were reduced to a minimum.

DATA COLLECTION

The study was conducted at the Department of Adaptive Bio-Signal Analysis at the University of Applied Sciences, Schmalkalden (Germany). In each trial, a volunteer had to accomplish a series of driving simulations. The driving situation was laid out for monotony in order to catalyze fatigue: the task was to simply hold the lane on a road without intersections, crossroads or any other cars present through a landscape at dark night at high speed. Before a trial, a volunteer carried an activity monitor and completed a sleep/wake log for at least 24 hours prior to the trial. A volunteer arrived at the lab at 10:00 pm. After wire-up, checking logs and activity monitors, experiment sessions started at 11:30 pm. There were eight experiment sessions in one trial, each lasting one hour, thus the last session finished at 8:30 am. Volunteers had a 1-hour break at 3:30 am. Each session included a 40-minute driving task, a 10-minute Compensatory Tracking Task (CTT), and a 5-minute Psychomotoric Vigilance Test (PVT). A total of 5 volunteers participated in the study, each whom completed two separate trials.

DATA ANALYSIS

Fatigue Measures

Driving Sessions. During each 40-minute driving session (eight driving sessions per trial), the following parameter set (fatigue measure: *definitions* in italics, (labels) in parenthesis) allowed to capture the different facets of driver fatigue:

- Typical signs of *micro-sleep events* (MSE) are prolonged eyelid closures, rolling eye movements, head nodding, and stare gaze. MSE are an objective, individually specific fatigue measure. The occurrence and severity of MSE was visually scored and logged during driving, resulting in a *weighted sum of MSE* per driving session.
- Lateral lane deviation is a continuously recorded measure of driving performance. The *standard deviation of lateral lane deviation* (LaneDev) over an entire driving session forms another objective.
- Accident events represent the consequences of the inability to stay awake and keep the lane. The measure (Acc) is the *number of accident events* over an entire driving session.
- The *Karolinska Sleepiness Scale* is a standardized, subjective and independent measure of fatigue on a numeric scale between 1 and 10, which the volunteer stated verbally every four minutes during driving. Those values were *averaged* per driving session (KSS).
- *Percentage of eyelid closure*, or PERCLOS promoted for many years as an excellent objective measure of fatigue was continuously recorded by a commercially available eye-tracking system. The average of PERCLOS over a driving session is called (PERCL).

CTT Sessions. The Compensatory Tracking Task (Van Orden et al. 2000) is a two-dimensional visual-motoric performance task involving a target positioned in the center of a display and a moving disk. The task is to keep the disk as near to the center of the target annulus as possible, using a trackball whose movement induces a restorative force to the disk in the direction of the trackball motion. The task was performed for 10 minutes. The position of the disk is recorded as a function of its previous position and velocity. The *mean and standard deviation of distance of the moving disk to the target* (M/SD Dist), the *mean and standard deviation of velocity of the*

disk (M/SD Velc) and the *mean and standard deviation of force applied to the disk* (M/SD Force) are used as set of CTT fatigue measures.

PVT Sessions. The Psychomotoric Vigilance Test (PVT) is a reaction task: the subject is instructed to respond to a visual stimulus (that is given in random intervals) with a button-push as quickly as possible. The PVT used in our study was the short 5-minute version evaluated in Lamond et al. (2005). Latency is defined as the *time duration between the appearance of the stimulus and the response.* The *mean and standard deviation of latency* (M/SD Latc) as well as the number of lapses, i.e. the *absence of a response*, were selected as set of PVT fatigue measures.

Heart Rate Measures

The position of R-peaks (i.e. heart beats) was detected in electrocardiogram (ECG) recordings. Calculating the time interval between consecutive beats results in an RR-interval time series with characteristic patterns and frequency contents. Artifacts or variant beats were excluded or corrected, respectively, by a thorough visual inspection of each series.

Time Domain. For a segment of RR intervals – each during driving, CTT and PVT – the simplest measures are its mean and standard deviation, which we denote as *heart rate* (HR) and *heart rate variability* (HRV), respectively. All consecutive *RR intervals differing more than 50 milliseconds were counted and normalized* by the length of the RR intervals segment, resulting in the measure (pNN50). After z-transforming the RR series, its *zero-crossings were counted and normalized* as well (ZeroCross).

Phase Space. Levy (1977) showed a clear nonlinear relation between sympathetic and parasympathetic activity at one side and HR at the other. A simple method to capture this nonlinear characteristic is the so-called *Poincaré plot* in phase space. It is both a useful visual tool which can summarize an entire RR series and a quantitative technique. A Poincaré plot of RR intervals is composed of points (RR_i, RR_{i+1}), that is each point in the plot corresponds to two consecutive RR intervals. The resulting cloud of points (see Figure 1) is usually characterized by two common descriptors: its *length along the line of identity* (SD2, describes long-term HRV) and its *breadth across this line* (SD1, describes short-term HRV). In most Poincaré plots of RR intervals, there is a visible and statistically highly significant asymmetry (Piskorski & Guzik 2007), with the upper part (decelerations) larger than the lower part (accelerations). In order to quantify those asymmetries, the Poincaré data distribution is transformed into Cartesian coordinates and then divided into four quadrants. In each quadrant, short- and long-term variations are calculated, resulting in the following 8 local descriptors (see Figure 2):

- Acceleration along major axis (SD1a_right & SD2a_right)
- Acceleration along minor axis (SD1a_low & SD2a_low)
- *Deceleration along major axis* (SD1d_left & SD2d_left)
- Deceleration along minor axis (SD1d_high & SD2d_high)

To express asymmetries between the four quadrants, the following 4 asymmetry properties are established from the local descriptors:

- Asymmetry ratios of opposite quadrants: SD1AS = <u>SD1a_right - SD1d_left</u> SD1
 , SD2AS = <u>SD2a_low - SD2d_high</u> SD2
 <u>SD2</u>
 Asymmetry ratios of quadrants on the same sides
 <u>SD2</u>
 <u><u>SD2</u>
 <u><u>SD2</u>
 <u><u>SD2</u>
 <u><u>SD2</u>
 <u><u>SD2</u>
 <u>(</u>
 <u>(</u>
 </u></u></u></u></u>
- Asymmetry ratios of quadrants on the same side: $SD1ASS = \frac{SD1a_low - SD1d_high}{SD1}$, $SD2ASS = \frac{SD2a_right - SD2d_left}{SD2}$




Figure 1. An example of Poincaré plot of RR intervals with fitted ellipse; (Diagonal dotted line, the "identity line" helps divide all points to decelerations or accelerations)




Figure 2. Poincaré plot of RR intervals during 40 minutes of driving session, in Cartesian coordinates with various asymmetric properties of short- & long-term HRV

These asymmetric properties are also calculated without being normalized against the global descriptors SD1 & SD2, resulting in the according asymmetries:

- SD1a_right- SD1d_left
- SD2a_low- SD2d_high
- SD1a_low- SD1d_high
- SD2a_right- SD2d_left

Comparison of heart rate measures and fatigue measures

Correlation coefficients between individual HR- and fatigue measures were computed. For each coefficient, session values of both trials (i.e. 16 sessions) of a HR and a fatigue measures were correlated. This approach averages (and therefore neglects) the intra-individual differences between both trials of each volunteer. In the next step, inter-individual differences were averaged in order to reveal universal coherences between HR- and fatigue measures. First, all session values (i.e. 16 sessions) of each measure of each subject were z-scored. Then, each session value of each measure was averaged over all 5 subjects. Finally, correlations were computed by pairing session values of each HR-measures with respective session values of each fatigue measure. Correlations were considered significant for p-values < 0.01.

RESULTS

As stated in our previous report (Hefner et al. 2009), the fatigue measures of driving, CTT and PVT generally show a clear time-on-task and a modest time-of-day behaviour: fatigue is low during first sessions and significantly higher in the second half of the trial. Maximum fatigue occurs during the third- or second-to-last session, between 5:30 and 7:30 pm. In order to correlate well with fatigue measures, the HR-measures would have to follow this course (or exactly vice versa, in case of negative correlation).

Tables 1-3 present a selection of individual correlation patterns. Inter-individual differences between the subjects are most obvious; the discrepancies are as extreme as for subjects 1 and 5 (Tables 1 and 3); where for the former almost a third of all fatigue and HR-measures correlate significantly, whereas for the latter no (except one) combination of HR- and fatigue measure exhibits significance. Table 4 reveals that the best coherence between HR- and fatigue measures is obtained for the asymmetry properties of long-term HRV (SD2[...]) and lateral lane deviation, respectively. Lane deviation and accident score generally show the same correlation patterns, since both are highly inter-dependent. Also, CTT and PVT measures, mainly distance and latency, respectively, correlate well with asymmetry properties of long-term HRV, even though in smaller number. None of the asymmetry ratios of long-term HRV correlates with any fatigue measures. Also, one exception aside, there's no correlation between measures of short-term HRV (SD1[...]) and fatigue. In the time domain, two different expressions of heart rate variability, standard deviation (HRV) and ZeroCross, show the same good correlation behaviour; mean heart rate (HR) and pNN50, on the other hand, are insignificant. Overall, the HR-measure ZeroCross exhibits the best coherence with fatigue measures.

CONCLUSIONS

The analysis of asymmetric properties of HRV confirms that long-term HRV in general correlates well with selected fatigue measures, but it didn't reveal further details as to where this link originates (e.g. from acceleration or deceleration of the heart rate). One the other hand, it is pleasant that a systematic coherence of long-term HRV to selected fatigue measures could be established from a group of subjects despite their huge inter-individual differences. For the CTT and PVT condition, the expectation that distance and latency, respectively, will relate well to HR-measures was supported. On the other hand, it is curious that for the driving condition only lateral lane deviation (and accident score, its close relative) exhibits good correlations to HRmeasures. Particularly MSE and KSS were expected to correlate well with HR-measures, since both have been proven to be reliable measures for fatigue (Sommer et al. 2009). A possible explanation might be that the time courses of MSE and KSS on one hand and of HR-measures on the other are linked by a nonlinear relationship that cannot be revealed by correlation analysis. The strong coherence between long-term HRV properties and specific fatigue measures suggests the possibility to predict driver and operator fatigue in the middle-term (around 30 minutes) solely from recordings of heart rate. Future analysis will show if these results will hold true for larger study populations.

	Driving							CI	PVT					
p < 0.01	MSE	Acc	KSS	LaneDev	PERCL	M Dist	SD Dist	M Velc	SD Velc	M Force	SD Force	M Late	SD Late	Lapses
HR	0.5788	0.5495	0.6290	0.6213	0.2099	0.5466	0.4443	0.3778	0.2831	-0.1851	-0.0854	0.5466	0.4443	0.3778
HRV	0.3378	0.7910	0.3399	0.8591	0.0010	0.7463	0.7043	0.7177	0.6430	0.3647	0.4167	0.7463	0.7043	0.7177
pNN50	0.2319	0.6472	0.3997	0.7204	-0.1009	0.6883	0.5789	0.5217	0.3908	-0.0158	0.0577	0.6883	0.5789	0.5217
ZeroCross	-0.3131	-0.6874	-0.3157	-0.7530	0.0303	0.0811	0.0661	-0.0616	-0.0701	-0.3989	-0.2976	0.0811	0.0661	-0.0616
SD1	0.3245	0.7387	0.4715	0.7222	0.0152	0.7729	0.6710	0.5926	0.4534	-0.0705	0.0490	0.7729	0.6710	0.5926
SD1a_right	0.4648	0.7712	0.4803	0.7041	0.0820	0.7854	0.6938	0.6172	0.4771	-0.0398	0.0665	0.7854	0.6938	0.6172
SD1d_left	0.2852	0.7058	0.4442	0.6473	0.1069	0.7854	0.7112	0.6500	0.5276	0.0457	0.1486	0.7854	0.7112	0.6500
SD1a_low	0.3035	0.6117	0.4051	0.7327	0.0374	0.4797	0.3555	0.3375	0.2270	-0.1170	-0.0799	0.4797	0.3555	0.3375
SD1d_high	0.3782	0.6902	0.5316	0.6226	0.1398	0.8185	0.7506	0.6710	0.5468	0.0443	0.1636	0.8185	0.7506	0.6710
SD1AS	0.2517	-0.0027	0.0792	0.0398	0.0069	-0.0647	-0.1246	-0.1157	-0.1857	-0.1896	-0.1762	-0.0647	-0.1246	-0.1157
SD1ASS	-0.4610	-0.2538	-0.3506	-0.0875	-0.5523	-0.7154	-0.7779	-0.7244	-0.7116	-0.4468	-0.5294	-0.7154	-0.7779	-0.7244
SD2	0.3383	0.7861	0.3336	0.8565	0.0012	0.7301	0.6909	0.7095	0.6397	0.3809	0.4284	0.7301	0.6909	0.7095
SD2a_right	0.3565	0.8069	0.3373	0.8651	0.0173	0.7416	0.7015	0.7162	0.6492	0.3711	0.4243	0.7416	0.7015	0.7162
SD2d_left	0.3212	0.7644	0.3295	0.8436	-0.0099	0.7127	0.6756	0.6975	0.6248	0.3936	0.4329	0.7127	0.6756	0.6975
SD2a_low	0.2550	0.7593	0.2268	0.8420	-0.1196	0.7047	0.6606	0.6458	0.5851	0.2700	0.3329	0.7047	0.6606	0.6458
SD2d_high	0.5596	0,6606	0.3935	0.6956	0.3053	0.6948	0.6942	0.7054	0.6725	0.4354	0.4776	0.6948	0.6942	0.7054
SD2AS	-0.2855	-0.0001	-0.1746	0.1390	-0.4556	-0.0721	-0.1315	-0.1753	-0.2209	-0.3121	-0.2812	-0.0721	-0.1315	-0.1753
SD2ASS	0.3572	0.2995	0.1832	0.1860	0.2883	0.4888	0.4568	0.4255	0.4317	0.0868	0.1975	0.4888	0.4568	0.4255
SD1a_right-SD1d_left	0.1401	-0.1534	-0.0704	-0.1263	-0.0492	-0.2774	-0.2952	-0.2850	-0.2904	-0.1657	-0.2196	-0.2774	-0.2952	-0.2850
SD2a_low-SD2d_high	-0.1157	0.1943	-0.0404	0.3588	-0.3418	-0.0113	-0.0529	-0.0770	-0.1065	-0.1587	-0.1720	-0.0113	-0.0529	-0.0770
SD1a_low-SD1d_high	-0.4621	-0.2630	-0.3597	-0.1007	-0.5548	-0.7484	-0.7849	-0.7110	-0.6681	-0.3255	-0.4326	-0.7484	-0.7849	-0.7110
SD2a_right-SD2d_left	0.4683	0.4626	0.2911	0.3256	0.3197	0.6409	0.5848	0.5411	0.5026	0.0707	0.2057	0.6409	0.5848	0.5411

Table 1. Correlation coefficients between HR- and fatigue measures for subject 1

Table 2. Correlation coefficients between HR- and fatigue measures for subject 3

	Driving							CI	PVT					
p < 0.01	MSE	Acc	KSS	LaneDev	PERCL	M Dist	SD Dist	M Velc	SD Velc	M Force	SD Force	M Late	SD Late	Lapses
HR	-0.0103	0.0012	0.1398	0.0225	0.0100	0.5481	0.5767	0.0118	-0.3032	-0,5239	-0,4060	0.5481	0.5767	0.0118
HRV	0.4843	0.6152	0.6576	0.6846	0.1932	0.4509	0.5926	0.3183	0.2109	-0.2422	0.0983	0.4509	0.5926	0.3183
pNN50	0.3743	0.4269	0.4272	0.4939	0.1047	0.8055	0.8520	0.4282	0.1256	-0.2592	0.0306	0.8055	0.8520	0.4282
ZeroCross	-0.4096	-0.5552	-0.6933	-0.6284	-0.2028	0.3538	0.2794	0.0139	-0.1659	-0.0127	-0.1461	0.3538	0.2794	0.0139
SD1	0.4417	0.4907	0.5160	0.5736	0.0918	0.7199	0.7706	0.3356	0.1198	-0.2512	0.0457	0.7199	0.7706	0.3356
SD1a_right	0.7047	0.7147	0.7241	0.7537	0.3212	0.7245	0.8037	0.4006	0.2188	-0.1527	0.2164	0.7245	0.8037	0.4006
SD1d_left	0,2901	0.3357	0.3929	0.4398	-0.0400	0.5681	0.6095	0.3045	0.1476	-0.1670	0.0604	0.5681	0.6095	0.3045
SD1a_low	0.3513	0.3922	0.3436	0.3976	0.0853	0.5822	0.6343	0.0150	-0.2372	-0.4899	-0.3220	0.5822	0.6343	0.0150
SD1d_high	0.4581	0.4863	0.5887	0.6179	0.0827	0.5334	0.5713	0.5061	0.4261	0.1027	0.4038	0.5334	0.5713	0.5061
SD1AS	0.6332	0.5936	0.5244	0.5063	0.5392	0.3455	0.3860	0.1955	0.1032	-0.0289	0.2086	0.3455	0.3860	0.1955
SD1ASS	-0.1815	-0.1234	-0.3500	-0.2617	0.0225	0.0505	0.0839	-0.3733	-0.5093	-0.4777	-0.5621	0.0505	0.0839	-0.3733
SD2	0.4863	0.6257	0.6707	0.6933	0.2033	0.3984	0.5470	0.3116	0.2232	-0.2332	0.1066	0.3984	0.5470	0.3116
SD2a_right	0.4587	0.5990	0.6522	0.6619	0.1943	0.3931	0.5358	0.2923	0.1959	-0.2601	0.0817	0.3931	0.5358	0.2923
SD2d_left	0.5194	0.6563	0.6947	0.7281	0.2155	0.3999	0.5563	0.3259	0.2497	-0.2013	0.1328	0.3999	0.5563	0.3259
SD2a_low	0.4834	0.5679	0.5999	0.6088	0.1663	0.5765	0.6700	0.1382	-0.0935	-0.4944	-0.2396	0.5765	0.6700	0.1382
SD2d_high	0.5010	0.6375	0.6898	0.7147	0.2528	0.0821	0.2664	0.4474	0.5339	0.2241	0.4723	0.0821	0.2664	0.4474
SD2AS	-0.1941	-0.2836	-0.4387	-0.3855	-0.1871	0.5182	0.5326	-0.1123	-0.4255	-0.5829	-0.5222	0.5182	0.5326	-0.1123
SD2ASS	-0.6716	-0.6995	-0.5549	-0.7549	-0.2110	0.0062	-0.1266	-0.0823	-0.1000	-0.3470	-0.1578	0.0062	-0.1266	-0.0823
SD1a_right-SD1d_left	0.4293	0.3838	0.3001	0.2704	0.4863	0.0810	0.1128	0.0651	0.0577	0.0648	0.1870	0.0810	0.1128	0.0651
SD2a_low-SD2d_high	-0.0663	-0.1103	-0.1892	-0.1874	-0.1045	0.5397	0.5960	-0.0346	-0.3140	-0,5655	-0.4359	0.5397	0.5960	-0.0346
SD1a_low-SD1d_high	-0.1953	-0.1505	-0.3250	-0.2913	0.0382	0.1141	0.1323	-0.3768	-0.5388	-0.5557	-0.6058	0.1141	0.1323	-0.3768
SD2a_right-SD2d_left	-0.4713	-0.4717	-0.2354	-0.5080	-0.0810	0.0521	-0.0642	-0.0551	-0.0794	-0.3692	-0.1464	0.0521	-0.0642	-0.0551

Table 3. Correlation coefficients between HR- and fatigue measures for subject 5

				PVT										
p < 0.01	MSE	Acc	KSS	LaneDev	PERCL	M Dist	SD Dist	M Velc	SD Velc	M Force	SD Force	M Late	SD Late	Lapses
HR	0.2987	0.2821	0.2685	0.2678	0.3018	0.1789	0.1478	-0.1337	-0.2389	-0.1969	-0.2490	0.1789	0.1478	-0.1337
HRV	0.5049	0.5151	0.3480	0.5305	0.0716	0.2148	0.2291	0.0852	0.0788	0.0113	0.0686	0.2148	0.2291	0.0852
pNN50	0.1427	0.1448	0.0437	0.0730	0.2433	0.1211	0.1058	-0.2738	-0.1874	-0.2991	-0.1562	0.1211	0.1058	-0.2738
ZeroCross	-0.3796	-0.4020	-0.4052	-0.2715	0.0969	-0.3408	-0.3154	-0.4297	-0.3285	-0.3167	-0.2267	-0.3408	-0.3154	-0.4297
SD1	0.2469	0.2617	-0.0186	0.1005	-0.0148	0.0817	0.0650	-0.2220	-0.2296	-0.2870	-0.2028	0.0817	0.0650	-0.2220
SD1a_right	0.3076	0.3278	-0.0226	0.1607	0.0450	0.0922	0.1185	-0.0616	-0.1039	-0.0896	-0.0650	0.0922	0.1185	-0.0616
SD1d_left	0.2421	0.2612	-0.1692	0.0689	-0.3003	-0.0557	-0.0932	-0.2903	-0.3185	-0.3481	-0.2959	-0.0557	-0.0932	-0.2903
SD1a_low	0.1722	0.1908	-0.0094	0.1273	0.1188	0.0483	0.0415	-0.1733	-0.2335	-0.2409	-0.2221	0.0483	0.0415	-0.1733
SD1d_high	0.2789	0,2897	-0,0042	0.0794	-0.0828	0.0705	0.0512	-0.2450	-0.2030	-0.2908	-0.1597	0.0705	0.0512	-0.2450
SD1AS	-0.1268	-0.1323	0.2981	0.1211	0.5955	0.1806	0.2635	0.3790	0.4021	0.4235	0.4124	0.1806	0.2635	0.3790
SD1ASS	-0,2900	-0.2818	-0.0553	-0.0345	0.2485	0.0768	0.0853	0.1620	0.0282	0.0925	-0.0436	0.0768	0.0853	0.1620
SD2	0,5065	0,5168	0.4209	0.5521	0.1105	0.2372	0.2522	0.1280	0.1216	0.0528	0.1039	0.2372	0.2522	0.1280
SD2a_right	0.4979	0.5058	0.3696	0.5540	0.0854	0.2048	0.2280	0.1193	0.1216	0.0461	0.1088	0.2048	0.2280	0.1193
SD2d_left	0.5155	0,5276	0.4879	0,5526	0.1471	0.2782	0.2866	0.1517	0.1346	0.0753	0.1088	0.2782	0.2866	0.1517
SD2a_low	0.4679	0.4651	0.4039	0.6960	0.2856	0.1477	0.2138	0.2022	0.2769	0.1995	0.2440	0.1477	0.2138	0.2022
SD2d_high	0.5220	0.5282	0.2621	0.3593	-0.1375	0.2368	0.2066	-0.0212	-0.0656	-0.1250	-0.0535	0.2368	0.2066	-0.0212
SD2AS	-0.2682	-0.2858	0.0038	0.0869	0.3049	0.0163	0.1000	0.2831	0.4348	0.3842	0.3601	0.0163	0.1000	0.2831
SD2ASS	-0.3023	-0.3444	-0.5357	-0.2182	-0.3066	-0.3944	-0.3793	-0.2759	-0.1571	-0.2628	-0.0884	-0.3944	-0.3793	-0.2759
SD1a_right-SD1d_left	-0.1253	-0.1382	0.2995	0.0906	0.5549	0.2871	0.3624	0.4828	0.4612	0.4923	0.4331	0.2871	0.3624	0.4828
SD2a_low-SD2d_high	-0.0219	-0.0417	0.1961	0.2852	0.3276	0.0031	0.1126	0.2909	0.4609	0.4019	0.4021	0.0031	0.1126	0.2909
SD1a_low-SD1d_high	-0.2989	-0.2944	-0.0299	-0.0335	0.2640	0.0454	0.0729	0.1658	0.0368	0.1299	-0.0311	0.0454	0.0729	0.1658
SD2a_right-SD2d_left	-0.2571	-0.2993	-0.4386	-0.1358	-0.2807	-0.4497	-0.3952	-0.2438	-0.0780	-0.1811	0.0077	-0.4497	-0.3952	-0.2438

	Driving							PVT						
p < 0.01	MSE	Acc	KSS	LaneDev	PERCL	M Dist	SD Dist	M Velc	SD Velc	M Force	SD Force	M Late	SD Late	Lapses
HR	0.3560	0.0364	0.4260	0.0250	0.5940	0.2789	0.1925	-0.1281	-0.2332	-0.7108	-0.3760	0.2068	0.1867	-0.3961
HRV	0.4167	0.7408	0.3883	0.6807	0.3345	0.6015	0.5685	0.2931	0.1769	-0.3187	0.0170	0.6609	0.5823	0.0292
pNN50	-0.0069	0.0550	0.0767	-0.0027	0.2091	0.2306	0.1525	-0.0552	-0.1615	-0.5386	-0.2471	-0.5220	-0.3656	0.0675
ZeroCross	-0.5747	-0.8394	-0.5521	-0.9037	-0.2909	-0.7253	-0.7042	-0.6550	-0.5334	-0.2624	-0.4319	-0.7728	-0.6689	-0.2249
SD1	0.1329	0.2129	0.1980	0.1460	0.2223	0.2395	0.1657	-0.0954	-0.1763	-0.5908	-0.2548	-0.5762	-0.4631	0.0301
SD1a_right	0.2999	0.4407	0.3455	0.3848	0.3539	0.4446	0.3821	0.1516	0.0432	-0.4552	-0.0931	-0.4049	-0.3989	-0.1109
SD1d_left	0.0781	0,1861	0.1437	0.1222	0.0966	0.1927	0.1184	-0.1278	-0.2043	-0.5559	-0.2484	-0.5717	-0.4768	0.0452
SD1a_low	0.1046	0.0543	0.1937	0.0321	0.2730	0.0865	0.0206	-0.2210	-0.3032	-0.6439	-0.4471	-0.5893	-0.4655	-0.0448
SD1d_high	0.1981	0.2921	0.2580	0.2385	0.2474	0.2057	0.1431	-0.0583	-0.0828	-0.4470	-0.0902	-0.3796	-0.3299	-0.0104
SD1AS	0.3911	0.2839	0.3221	0.3616	0.4301	0.4647	0.4508	0.4937	0.3758	0.0951	0.2276	0.0231	-0.0956	-0.1461
SD1ASS	-0.3030	-0.4476	-0.3294	-0.4185	-0.1288	-0.3359	-0.3423	-0.3991	-0.4069	-0.2963	-0.4843	-0.4697	-0.3775	-0.1864
SD2	0.4559	0.7732	0.4283	0.7265	0.3572	0.6359	0.6084	0.3380	0.2259	-0.2792	0.0585	0.7181	0.6326	0.0540
SD2a_right	0.4437	0.7601	0.4128	0.6991	0.3481	0.5886	0.5599	0.2952	0.1822	-0.3106	0.0226	0.6773	0.6094	0.1028
SD2d_left	0.4855	0.7897	0.4624	0.7654	0.3821	0.6885	0.6609	0.3896	0.2835	-0.2362	0.1074	0.7547	0.6582	-0.0206
SD2a_low	0.4095	0.7504	0.3382	0.7087	0.3386	0.6695	0.6435	0.3824	0.2939	-0.2310	0.1130	0.5180	0.4889	0.2800
SD2d_high	0.4897	0.6874	0.5138	0.6585	0.3891	0.3979	0.3662	0.1332	0.0253	-0.3154	-0.0357	0.6136	0.5806	0.0201
SD2AS	-0.3357	-0.1859	-0.4682	-0.2277	-0.2451	0.3186	0.2783	0.1796	0.1092	-0.1727	0.0006	-0.3570	-0.4043	-0.2237
SD2ASS	-0.2134	-0.4149	-0.1985	-0.4913	0.0282	-0.3029	-0.3575	-0.3109	-0.3641	-0.3930	-0.2939	0.0917	0.1075	0.2290
SD1a_right-SD1d_left	0.2196	0.1313	0.1577	0.2247	0.2840	0.4046	0.4045	0.4566	0.3847	0.1373	0.2509	0.1669	0.0238	-0.1132
SD2a_low-SD2d_high	-0.1187	0.0121	-0.2721	-0.0328	-0,0666	0.4306	0.3815	0.1838	0.1184	-0.2789	-0.0352	-0.0436	-0.1331	-0.1306
SD1a_low-SD1d_high	-0.3182	-0.4444	-0.3380	-0.3931	-0.2079	-0.2196	-0.2396	-0.2628	-0.3019	-0.2394	-0.4103	-0.3847	-0.2799	0.0286
SD2a right-SD2d left	0.0115	-0.2247	0.0313	-0.2837	0.2330	-0.2167	-0.2602	-0.2033	-0.2761	-0.3291	-0.1978	0.1223	0.1300	0.1656

Table 4. Correlation coefficients between HR- and fatigue measures for the entire subject group

Note: Significant values are marked gray

REFERENCES

- Coumel P, Maison-Blanche P, Catuli D (1995) Heart rate and heart rate variability, in *Heart rate variability*. Malik M, Camm AJ (eds.), Futura Publishing Company, Inc.
- Lamond N, Dawson D, Roach GD (2005) Fatigue Assessment in the Field: Validation of a Hand-Held Electronic Psychomotor Vigilance Task. *Aviation, Space, and Environmental Medicine,* 76.
- Levy MN (1977) Parasympathetic control of the heart, in *Neural Regulation of the Heart*. Randall WC (ed.), Oxford University Press, New York.
- Hefner R, Edwards D, Heinze C, Sommer D, Golz M, Sirois B, Trutschel U (2009) Operator Fatigue Estimation Using Heart Rate Measures. Proc 5th Int Driving Symp Human Factors Driver Assessment Training Vehicle Design. Big Sky/Montana, USA, pp 110–117.
- Piskorski J, Guzik P (2007) Geometry of the Poincaré plot of RR intervals and its asymmetry in healthy adults. *Physiol. Meas.*, 28, pp 287–300.
- Sommer D, Golz M, Schnupp T, Krajewski J, Trutschel U, Edwards D (2009) A Measure of Strong Driver Fatigue. Proc 5th Int Driving Symp Human Factors Driver Assessment Training Vehicle Design, Big Sky/Montana, USA, pp 9–15.
- Van Orden KF, Jung TP, Makeig S (2000) Combined eye activity measures accurately estimate changes in sustained visual task performance. *Biological Psychology*, 52, pp 221–240.